


GFCI 2 FT 20 AMP IN-LINE GFCI W/SINGLE CONNECTORS



30396002-08



NEMA 5-20R

SIMILAR MODELS

MODEL 30396003-08
2 FT 20 AMP IN-LINE
GFCI W/SINGLE CON-
NECTORS (20 AMP
TWIST LOCK)

30396500-08
USER ATTACHABLE 20
AMP IN-LINE GFCI

Tower's 2 ft 20 Amp In-line GFCI
w/single connectors
Model 30396002-08 manual reset GFCI
with provide GFCI protection for tools
and equipment rated up to 20 amps.

The connectors are NEMA 5-20 P&R
straight bladed which will only plug into
a 20 amp outlet or female connector.

The bright "Red" light indicates when
the power is "ON". The TEST and RESET
buttons allow for periodic testing.

FEATURES

MODEL 30396002-08

- 12/3 gauge STJW cord
- Trip level 4-6 mA
- UL and CUL listed
- Manual reset
- UL rainproof rated for outdoor use
- Complies with all OSHA regulations

SPECIFICATIONS

- Class "A" people protection GFCI
- Rated for 125 volt, 20amp use
- 2500 watts, 60 Hz
- LED Power "ON" indicator
- Open neutral and ground neutral protection
- Operating temperature range -35 degree C to 66 degree C
- Impact resistant case