

## **GFCI 25, 50 & 100 FT IN-LINE GFCI & TRIPLE TAP**

**Tower's 25, 50 & 100 ft. In-line GFCI with triple tap**



**30438302,  
30438303  
&  
30438306**

These models can be use as an OSHA compliant industrial cord set for any maintenance activities with power tools and equipment.

This product is ruggedly made for indoor or outdoor use. The molded triple tap connector provides GFCI protection to multiple devices.

The bright “Red” light indicates when the power is “ON”. The TEST and RESET buttons allow for periodic testing.

### **FEATURES**

**MODEL 30438302, 30438303 & 30438306**

- 12/3 gauge STJW cord
- Trip level 4-6 mA
- UL and CUL listed
- Automatic reset
- UL rainproof rated for outdoor use
- Complies with all OSHA regulations

### **SIMILAR MODELS**

**MODEL 30438024  
2 FT IN-LINE GFCI &  
TRIPLE TAP**

**MODEL 30438326  
2 FT IN-LINE GFCI &  
TRIPLE TAP w/ Lighted  
End**

### **SPECIFICATIONS**

- Class “A” people protection GFCI
- Rated for 125 volt, 15 amp use
- 1875 watts, 60 Hz
- LED Power “ON” indicator
- Open neutral and ground neutral protection
- Operating temperature range  
-35 degree C to 66 degree C
- Impact resistant case