GFCI - 3 FT 20 AMP IN-LINE GFCI WITH SINGLE LOCKING CONNECTORS



30396003-08



NEMA L 5-20R

SIMILAR MODELS

MODEL 30396002-08 2 FT 20 AMP IN-LINE GFCI W/SINGLE CON-NECTORS (20 AMP STRAIGHT BLADE\ CONNECTORS) 30396500-08 USER ATTACHABLE 20 AMP IN-LINE GFCI Tower's 3 ft. 20 Amp In-line GFCI w/single connectors Model 30396003-08 manual reset GFCI with provide GFCI protection for tools and equipment rated up to 20 amps.

The connectors are NEMA L 5-20 P&R twist lock style will only plug into a 20 amp twist lock outlet or female connector.

The bright "Red" light indicates when the power is "ON". The TEST and RESET buttons allow for periodic testing.

FEATURES

MODEL 30396003-08

- 12/3 gauge STJW cord
- Trip level 4-6 mA
- UL and CUL listed
- Manual reset
- UL rainproof rated for outdoor use
- Complies with all OSHA regulations

SPECIFICATIONS

- Class "A" people protection GFCI
- Rated for 125 volt, 20amp use
- 2500 watts, 60 Hz
- LED Power "ON" indicator
- Open neutral and ground neutral protection
- Operating temperature range -35 degree C to 66 degree C
- Impact resistant case