

GFCI 100 FT IN-LINE GFCI & TRIPLE TAP

Tower's 100 ft. In-line GFCI & triple tap



30438306

Model 30438306 can be used as an OSHA compliant industrial cord set for any maintenance activities with power tools and equipment. This product is ruggedly made for indoor or outdoor use. The molded triple tap connector provides GFCI protection to multiple devices. The bright “Red” light indicates when the power is “ON”. The TEST and RESET buttons allow for periodic testing.

FEATURES

MODEL 30438306

- 12/3 gauge STJW cord
- Trip level 4-6 mA
- UL and CUL listed
- Automatic reset
- UL rainproof rated for outdoor use
- Complies with all OSHA regulations

SIMILAR MODELS

MODEL 30438024
2 FT IN-LINE GFCI &
MODEL 30438327
15 FT IN-LINE GFCI &
MODEL 30438303
50 FT IN-LINE GFCI &
MODEL 30438303
50 FT IN-LINE GFCI
All with a Triple Tap Outlet

SPECIFICATIONS

- Class “A” people protection GFCI
- Rated for 125 volt, 15 amp use
- 1875 watts, 60 Hz
- LED Power “ON” indicator
- Open neutral and ground neutral protection
- Operating temperature range
-35 degree C to 66 degree C
- Impact resistant case